Thank you for purchasing our product, please read these instructions carefully before using it.

## I. Warning

- 1. Do not disassemble or repair this unit by yourself.
- 2. Do not use or store this unit in the following circumstances: high temperature, high humidity, dirty or strong shock places.
- 3. Do not drop off this unit or bump this unit off hard surface.
- 4. Do not use cleaning liquid or alcohol to clean this unit in case of damage.
- 5. Remove batteries if not using the unit for a long period of time.
- 6. Please dispose the used battery properly.

## II. Battery replacement

- 1. Press the front of the battery cover and then slide back to remove the cover. Take out the flat batteries.
- 2`Put the battery into the battery compartment by placing the negative(-) pole of battery facing inside. Insert the front of cover and then press down and push to close.

## III. How to use

- A. Connect the input jack with the guitar tightly, the effects pedal will start working then.
- B. DRIVE——Adjust the degree of distortion.
- C. TONE --- Adjust the intensity of the tone
- D. VOLUME --- Adjust the volume of the sound.
- E. LED will be in red light when the effect pedal in use. If no light or in the dim light, please change new battery.
- F. Power adapter——When use the power adapter, the battery supply will be cut off automatically.

## IV. Specifications

Input Impedance: 500K Ω
Output Impedance: 10K Ω
Running Current: 7ma

Power: 6F22 9V Battery/ DC 9V adapter Dimension:120(L)×72(W)×55(H) mm

Weight:280g