

Important Notice

Water leakage caused by wrong operation and LCD willful damage are not within the scope of free warranty.

Failure to follow these safety instructions could result in some unnecessary injuries or damage to Runbo phone . Please read all the safety information carefully below before using Runbo phone .

- Traffic safety

 Please do not use mobile phone while you are driving.
- Switch on Do not switch the device on when wireless phone use is safely prohibited or when it may cause interference or danger.
- In hospital Please obey the rules in the hospital, turning off the phone when it is forbidden near some medical instruments.
- On a plane please turn off your phone when you are on a plane because all the wireless devices can interfere with the plane.
- Gas station do not use the device near the gasoline station area
- Qualified Only professional repairman can open and repair the repairing device
- Accessories Only original spare parts and battery can be used on and battery this device

Parts Info







1 Navigation key	7 Number	13 LED cover
2 Select key	8 Receiver	14 Walkie talkie antenna cover
3 Back key	9 Microphone	15 USB cover
4 OK key/Torch	10 Walkie talkie key	16 Speaker
5 Dial key	11 SIM CARD slot	17 Holder screw hole
6 End key	12 Strape hole	

SIM installment



Insert SIM CARD:

- 1:Open the SIM card cover
- 2:Insert SIM card as shown in picture
- 3: Push the cover and close the cover properly



Assemble and disassemble spring clip:

1:use screw driver to assemble and disas semble spring clip.

USB connector



- Charge the mobile phone
- 1:Open the USB cover
- 2:Connect the data cable with USB connector.
- 3:Connect the data cable another connector with adapter
- 4: Charge the mobile phone

Caution:LED is shown orange while charging. When charging fully, the LED will show green.

Walkie Talkie installment





Install walkie talkie antenna

- 1:Open the walkie talkie antenna cover.
- 2:connect the walkie talkie antenna with the metal connector.

Walkie talkie guide:

Before using the walkie talkie.plz install walkie talkie antenna

1: Find and open the walkie talkie application in the menu.

2:user can scan or input RX and TX code. The device support 400- 470 mHZ (UHF) full range / 136–174 Mhz (VHF)

3:set the frequency and press ok key to start the walkie talkie application menu .

4:make the same channel and TX and RX setting between different devices.

 $5\mbox{:}\mbox{gap}$ range parameter: it refer to frequency gap from the start to next frequency.

6: Noise parameter: 1 means weak noise resistant and long distance receive capacity.

7:Standard SMA connector, easy to expand.

8: Support the repeater mode. Piz refer to related document.